

**Annexure 1 Price Schedule**

| Sl# | Item   | Specification   | Qty. | Unit | Place of Delivery                                   | Price per Unit (Nu) | Value (Nu) |
|-----|--|---|------|------|---|---------------------|------------|
| 1.  | <p align="center"><b>OM SYSTEM M.Zuiko<br/>Digital ED 150 - 600mm<br/>f/5.0 - 6.3 IS Lens (Micro<br/>Four Thirds Mount)</b></p>                  | <p><b>Lens Construction</b></p> <ul style="list-style-type: none"> <li>• Lens configuration: 25 elements/ 15 groups</li> <li>• Maximum image magnification: 0.35x (wide)/ 0.20x (tele)</li> <li>• Equiv.35mm: 0.70x (wide)/ 0.39x (tele)</li> <li>• Angle of view: 8.2 – 2.1°</li> <li>• Closest focusing distance: 0.56m (wide)/ 2.8m (tele)</li> <li>• Minimum field size: 49.4 x 37.1mm (wide)<br/>88.6 x 66.6mm (tele)</li> <li>• ED lens elements: 2 ED/ 4 Super ED</li> <li>• HR Elements: 6</li> <li>• HD Lens Elements: 1</li> </ul> <p><b>Focal length</b></p> <ul style="list-style-type: none"> <li>• Focal length: 150 – 600mm</li> <li>• Focal length (equiv. 35mm): 300 – 1200mm</li> </ul> <p><b>Aperture</b></p> <ul style="list-style-type: none"> <li>• Maximum aperture: F5.0 (wide)/ F6.3 (tele)</li> <li>• minimum aperture: F22</li> <li>• Number of aperture blades: 9 circular aperture diaphragm for natural background blurring</li> </ul> <p><b>Image Stabilizer</b></p> <ul style="list-style-type: none"> <li>• Modes: Two-dimensional, vertical or horizontal activation</li> <li>• Effective Compensation Range: Up to 7 EV steps* 5-axis Sync IS (wide)<br/>Up to 6 EV steps 5-axis Sync IS (tele)<br/>Up to 6 EV steps (Lens IS) (wide)<br/>Up to 5 EV steps (Lens IS) (tele)</li> <li>• Type: VCM</li> </ul> <p><b>Converter Combinations (MC-14)</b></p> <ul style="list-style-type: none"> <li>• Maximum image magnification: 0.50x (wide)/ 0.28x (tele)</li> <li>• (Equiv. 35mm): 0.99x (wide)/ 0.55x (tele)</li> <li>• Closest focusing distance: 0.58m (wide)/ 2.8m (tele)</li> <li>• Minimum field size: 34.9 x 26.2mm (wide)<br/>62.7 x 47.1mm (tele)</li> </ul> <p><b>Converter Combinations (MC-20)</b></p> <ul style="list-style-type: none"> <li>• Maximum image magnification: 0.70x (wide)/ 0.39x (tele)</li> <li>• (Equiv. 35mm): 1.4x (wide)/ 0.78x (tele)</li> <li>• Closest focusing distance: 0.59m (wide)/ 2.8m (tele)</li> <li>• Minimum field size: 24.7 x 18.5mm (wide)<br/>44.3 x 33.3mm (tele)</li> </ul> <p><b>Dimensions/Weight</b></p> <ul style="list-style-type: none"> <li>• Diameter: 109.4mm (greatest dimension)</li> <li>• Length: 264.4mm</li> <li>• Filter diameter: 95mm</li> <li>• Weight: 2065g</li> </ul> <p><b>Cover/Cap</b></p> <ul style="list-style-type: none"> <li>• Lens Cap: LC-95</li> <li>• Lens Hood: LH-103</li> </ul> <p><b>Sample or the brochure of the product required</b></p> | 01   | Nos. | WWF-<br>Bhutan<br>Office,<br>Kawajangsa,<br>Thimphu |                     |            |
| 2.  | <p><b>Lens Changer™ 150-600<br/>V3.0 Lens Pouch / Bag -</b><br/>Designed to fit 150-600 mm f/5–6.3 telephoto lenses, hood storage compatible</p> | <p><b>External Dimensions:</b> 5.8" W x 13.4" H x 5.9" D (14.7 x 34 x 15 cm)<br/><b>Internal Dimensions:</b> 5.5" W x 12.7" H x 5.6" D (14 x 32 x 14.2 cm)</p> <p><b>Sample or the brochure of the product required</b></p>   | 01   | Nos. |   |                     |            |